


B01220-00



Description

32-LED zone indication module

- LED module with 32 red / 32 yellow LEDs for zone indication
- For mounting behind front plate
- Zone LEDs programmable

Technical specifications :

Dimensions : 104 x 150 x 26 mm
(W x H x D)

VdS No. : G 205 024

B01230-00



Printer (Built-In version) with RS-232 interface and power supply

- Can be mounted in housing B1 and B2
- Interfacing to F2 Fire Alarm Control Panel by included RS-232 interface
- Thermal printer with 24 characters per line
- Controller and power supply included
- Memory 8 k RAM included for fast data transmission

Technical specifications :

Paper width : 58 mm
 Characters / line : 40
 Colour : grey
 Dimensions (W x H x D) : 85 x 85 x 55 mm

B01231-00

Spare paper role for Printer

- One role 58mm, diameter 37mm

B01330-00



Universal Relay card with 8 c/o contacts

- For universal applications but ideally for systems F1 and F2
- 8 programmable dry relay contacts (250V/5A)
- Pluggable terminals for easy service / wiring
- Activation e.g. by O/C output of loop card/ conventional detector card
- Possibility of "Unset Mode" in case of maintenance of the system

Technical specifications :

Quiescent current : 5 mA
 Contacts : 8 x change over
 Max. Load : 250V AC / 5 A
 Weight : 200 g
 Dimensions (W x H x D): 127 x 85 x 20 mm

VdS No. : G 205 024