

SC-51-0100-0001-99

SmartCell Fire Manual Call Point

Overview

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

SC-51-0100-0001-99

SmartCell Fire Manual Call Point

Technical specifications

General

| | |
|--------------------|-----------|
| Status indication | LED |
| Wireless frequency | 868 MHz |
| Compatibility | SmartCell |

Electrical

| | |
|-----------|--|
| Batteries | 2 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus) |
|-----------|--|

Physical

| | |
|---------------------|-----------------------------|
| Physical dimensions | 92 x 97 x 47 mm (W x H x D) |
| Net weight | 0.2 kg |
| Colour | Red |
| Mounting type | Wall mount |

Environmental

| | |
|-----------------------|----------------------------------|
| Operating temperature | -10 to +55°C |
| Storage temperature | -10 to +55°C (without batteries) |
| Relative humidity | 95% noncondensing max. |
| Environment | Indoor |

Regulatory

| | |
|---------------|-------------------------------|
| Compliance | CE |
| Certification | CPR |
| Standards | EN54-11 EN54-13 EN54-25 |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.