



TVN-2216P-4T

TruVision NVR 22P, H.265, 16 kanaler IP, 2 gigabitportar, 4 TB

Overview

TruVision NVR 22P (TVN 22) is a robust high performance H.264/H.265 network video recorder. With a total bandwidth of 256 Mbps (16-channel) or 320Mbps (32- and 64 channel) available, the TVN 22P is able to connect up to 16/32/64 IP cameras and provide real time recording (25/30 fps) at Full HD 1080p resolution on all channels simultaneously. With its fully flexible bandwidth allocation, the TVN 22P allows recording resolutions up to 8MPX at various frame rates.

Ease of use

TVN 22P was designed to make system configuration and overall use easier for both the installer and end-users through features such as: ezDDNS, start-up wizards, plug & play hard drives, auto discovery of natively supported cameras and is fully compatible with TruVision Navigator 6.0SP1 and TVRmobile 2.4.

H.265

The TVN 22P is supporting both H.264 and H.265 compression techniques. The H.265 compression is the next evolution of video encoding. Using H.265 will result in a reduced file size for the same video content and a reduced transmission bandwidth compared to H.264. This means that for the same storage capacity more video can be stored when using H.265 than H.264 encoding. To use the H.265 encoding in the TVN 22, H.265 cameras need to be used. H.265 will be available in the TruVision S4 IP cameras.


Ease of use

Thanks to its 2U housing, the maximum on-board storage capacity for the TVN 22P is 48TB, using eight six TB hard drives. The hard drives can be accessed via the lockable front panel door, allowing customers to easily expand storage as their system and/or requirements grow. Additionally, TVN 22P supports RAID 0,1,5,10 for storage redundancy. Recording options include continuous, event and alarm. The three modes can be combined, to ensure that the most efficient recording is possible.

TruVision OH

TVN 22P has the OH (Osborne-Hoffmann) alarmreceiver module embedded inside. The OH receiver is an alarm message receiver and can connect to up to three Interlogix IP intrusion panels that report in SIA or XSIA format.

Alarm messages, disarming and arming messages can be send from the alarm panel to the recorder, which then can take actions (trigger alarm recording, send a PTZ to a preset, run a shadow tour or preset tour, trigger an alarm output or send a notification message to TVRmobile). Also the heartbeat message between panel and recorder is monitored. This solution offers straightforward alarm verification and is free of charge.



Detaljer

- Linux embedded Play and Play configuration
- Up to 256/320 Mbps camera recording bandwidth
- Up to 16/32/64 channels to be connected
- Up to 48TB embedded storage (8x 6TB)
- RAID 0,1, 5,10 support
- Flip-open front panel for easy HDD access, servicing & expansion
- New icon based front pane
- Real-time Full HD recording
- Motion detection, VCA, privacy masking, tamper detection
- TruVision IP camera auto-discovery
- Third party camera support via ONVIF and PSIA
- IP camera configuration import/export
- Custom protocol configuration (RTSP streaming)
- Network redundancy
- Integration of Carrier IP intrusion panels via SIA/XSIA reporting
- Recorder failover functionality (one failover unit per 4 operational recorders)
- TVK-800 IP keypad support (H.265 is not supported by the TVK-800)
- USD DVD burner support
- TruVision Navigator license-free client/host or standalone application (6.0SP1)
- TVRmobile app for Android and iOS

TVN-2216P-4T

TruVision NVR 22P, H.265, 16 kanaler IP, 2 gigabitportar, 4 TB

Tekniska specifikationer

Video-/ljudingång

Edge failover-inspelning 16

Max. bandbredd per kanal 16 Mbps

Kamerabandbredd 256 Mbps

Max. IP-ljud in 16

Lokal översikt

OSD för synkron uppspelning (kanaler) Up to 16 channels

Omvänd uppspelning OSD (kanaler) 1

Fjärrövervakning

Total tillgänglig visningsbandbredd 256 Mbps

Max. live-strömmar 128

Max. spela upp visningsströmmar 128

Max. webbläsare för uppspelningsupplösning 8 MPX

Max. webbläsare för uppspelning samtidigt Max. 16 tiles (4x4)

Omvänd uppspelningswebbläsare (kanaler) Up to 9 channels, depending on PC performance

Lagring

SATA-gränssnitt 8

Maks. kapacitet per SATA HDD (TB) 8

Nätverk

Nätverkskort (NIC) 2

Network ports per NIC 1

Elektrisk

Strömförbrukning utan hårddisk (W) <=30 W



Fysisk

Fysiska dimensioner 442 x 442 x 92 mm (W x D x H)

Miljö

Driftstemperatur -10 to +55°C (14 °F to 131 °F)

Relativ luftfuktighet 10 to 90%



Carrier Fire & Security förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 18 April 2024 - 16:55