

## Uncoated Papers

- Toner
- Crystal Point
- Waterbased Inks
- UVgel/UV
- Latex

LFM154 Ribbed Kraft Unbleached  
70 g/m<sup>2</sup>

**Product Description** Narrow striped unbleached kraft paper made from 100% pure long fiber pulp. The smooth surface and consistent quality are ideal for digitally printing personalized gift wrapping paper or for producing smaller runs of wrapping paper. The production of paper carrier bags is also perfectly possible. Suitable for most roll-to-roll printers.

| Physical Properties | Thickness | 87 µm               | ISO 534  | Roughness Bendtsen  | 180 ml/min | ISO 8791-2 |
|---------------------|-----------|---------------------|----------|---------------------|------------|------------|
|                     | Weight    | 70 g/m <sup>2</sup> | ISO 536  | Porosity Bendtsen   | 90 ml/min  | ISO 8791-2 |
|                     | Opacity   | 99.9 %              | ISO 2471 | Stiffness L&W MD/CD | 38/70 mN   | ISO 2493-1 |

All values listed are target values

|                                   |  |  |
|-----------------------------------|--|--|
| <b>Applications/<br/>features</b> | Gift wrapping<br>Consumer (carrier)<br>bags<br>Indoor banners<br>Point-of-sale | Good runnability and folding properties<br>Machine smooth surface<br>Good flatness<br>High opacity<br>Recyclable |
|-----------------------------------|--|--|

**Available Widths (mm)** 3"core 1000 Refer for our current offering to [www.canon-europe.com/mediaguide](http://www.canon-europe.com/mediaguide)

Refer for our current offering to [www.canon-europe.com/mediaguide](http://www.canon-europe.com/mediaguide)

**Storage Conditions** Temperature 10-20°C, Relative Humidity 20-50%  
Relpack opened rolls when not in use.

**Environment** No Material Safety Data Sheet required.

| Lamination Compatibility | Cold | Warm | Hot | Cold: pressure sensitive<br>Warm: heat activated: 85°C - 95°C<br>Hot: heat activated: 105°C - 130°C |
|--------------------------|------|------|-----|---|
| yes                      | no   | no   |     |   |

**Outdoor Use** This paper is developed for indoor use.

**Colour Profiles** Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on [www.canon-europe.com/mediaguide](http://www.canon-europe.com/mediaguide)

**Processing  
Guidelines**

**Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing. It is recommended to handle the media with cotton gloves. Insert the paper with care in the printer. Incorrect loading can cause skewing or creasing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printer ink combinations. Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon media profiles include recommended ink restrictions and printer settings for Canon supported printers.

---

Standard disclaimer:  
All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.  
[canon.com](http://canon.com)  
Canon Europe  
[canon-europe.com](http://canon-europe.com)  
English edition 0615  
© Canon Europa N.V., 2022

**Canon**